UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.usplo.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/777,470	02/11/2004	Abraham Phillip Lee	703538.4033	2234
34313 7590 08/02/2007 ORRICK, HERRINGTON & SUTCLIFFE, LLP IP PROSECUTION DEPARTMENT			EXAMINER	
			MUI, CHRISTINE T	
4 PARK PLAZ SUITE 1600	A	•	ART UNIT	PAPER NUMBER
	IRVINE, CA 92614-2558		1709	
•		•		
			MAIL DATE	DELIVERY MODE
		•	08/02/2007	PAPER

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

	Application No.	Applicant(s)
Office Action Commence	10/777,470	LEE ET AL.
Office Action Summary	Examiner	Art Unit
	Christine T. Mui	1709
The MAILING DATE of this communication Period for Reply	n appears on the cover sheet with the	correspondence address
A SHORTENED STATUTORY PERIOD FOR REWHICHEVER IS LONGER, FROM THE MAILING - Extensions of time may be available under the provisions of 37 CF after SIX (6) MONTHS from the mailing date of this communication. If NO period for reply is specified above, the maximum statutory period of the reply within the set or extended period for reply will, by some and patent term adjustment. See 37 CFR 1.704(b).	G DATE OF THIS COMMUNICATION FR 1.136(a). In no event, however, may a reply be the normal state of the state	N. mely filed n the mailing date of this communication. ED (35 U.S.C. § 133).
Status		•
1)⊠ Responsive to communication(s) filed on 1 2a)□ This action is FINAL. 2b)⊠ 3)□ Since this application is in condition for all closed in accordance with the practice und	This action is non-final. owance except for formal matters, pr	
Disposition of Claims		
4) Claim(s) 1-41 is/are pending in the applica 4a) Of the above claim(s) is/are with 5) Claim(s) is/are allowed. 6) Claim(s) 1-41 is/are rejected. 7) Claim(s) is/are objected to. 8) Claim(s) are subject to restriction are	ndrawn from consideration.	
Application Papers		,
9)⊠ The specification is objected to by the Exam 10)⊠ The drawing(s) filed on 11 February 2004 is Applicant may not request that any objection to Replacement drawing sheet(s) including the co 11)□ The oath or declaration is objected to by the	s/are: a) accepted or b) objected or b) ob	e 37 CFR 1.85(a). njected to. See 37 CFR 1.121(d).
Priority under 35 U.S.C. § 119		
12) Acknowledgment is made of a claim for fore a) All b) Some * c) None of: 1. Certified copies of the priority docum 2. Certified copies of the priority docum 3. Copies of the certified copies of the priority docum application from the International Bu * See the attached detailed Office action for a	nents have been received. nents have been received in Applicat priority documents have been receiv reau (PCT Rule 17.2(a)).	ion No ed in this National Stage
Attachment(s) 1) Notice of References Cited (PTO-892) 2) Notice of Draftsperson's Patent Drawing Review (PTO-948) 3) Information Disclosure Statement(s) (PTO/SB/08) Paper No(s)/Mail Date 10 September 2004.	4) Interview Summary Paper No(s)/Mail D 5) Notice of Informal F 6) Other:	ate

Page 2

Application/Control Number: 10/777,470

Art Unit: 1709

DETAILED ACTION

Drawings

- The drawings are objected to as failing to comply with 37 CFR 1.84(p)(5) 1. because they include the following reference character(s) not mentioned in the description: in Figure 1, embodiment 39; in Figure 1, embodiment 36; in Figure 1, embodiment 42; in Figure 2, embodiment 130; in Figures 4A-C, embodiments 328, 422, 423, 424 and 426; in Figure 9, the embodiments 422, 423, 424, and 428; in Figure 13, embodiment '120 and in Figure 14 embodiment 135. Corrected drawing sheets in compliance with 37 CFR 1.121(d), or amendment to the specification to add the reference character(s) in the description in compliance with 37 CFR 1.121(b) are required in reply to the Office action to avoid abandonment of the application. Any amended replacement drawing sheet should include all of the figures appearing on the immediate prior version of the sheet, even if only one figure is being amended. Each drawing sheet submitted after the filing date of an application must be labeled in the top margin as either "Replacement Sheet" or "New Sheet" pursuant to 37 CFR 1.121(d). If the changes are not accepted by the examiner, the applicant will be notified and informed of any required corrective action in the next Office action. The objection to the drawings will not be held in abeyance.
- 2. The drawings are objected to under 37 CFR 1.83(a) because they fail to show the oil-water interface 127 in Figure 2, the down stream output channel 128 in Figure 2, the angle of entry θ_A and θ_B in Figures 3A-C and Figures 6A-C (just Figure 6 is shown) as described in the specification. Any structural detail that is essential for a proper

Art Unit: 1709

understanding of the disclosed invention should be shown in the drawing. MPEP § 608.02(d). Corrected drawing sheets in compliance with 37 CFR 1.121(d) are required in reply to the Office action to avoid abandonment of the application. Any amended replacement drawing sheet should include all of the figures appearing on the immediate prior version of the sheet, even if only one figure is being amended. The figure or figure number of an amended drawing should not be labeled as "amended." If a drawing figure is to be canceled, the appropriate figure must be removed from the replacement sheet, and where necessary, the remaining figures must be renumbered and appropriate changes made to the brief description of the several views of the drawings for consistency. Additional replacement sheets may be necessary to show the renumbering of the remaining figures. Each drawing sheet submitted after the filing date of an application must be labeled in the top margin as either "Replacement Sheet" or "New Sheet" pursuant to 37 CFR 1.121(d). If the changes are not accepted by the examiner, the applicant will be notified and informed of any required corrective action in the next Office action. The objection to the drawings will not be held in abeyance.

Specification

- 3. The disclosure is objected to because of the following informalities:
- 4. On page 7, [0036], line 1, the instance where it reads "Turning to Figure 1," should read "Turning to Figure 2,".

Art Unit: 1709

5. On page 19, [0072], line 1, the instance where it reads "as shown in Figures 21A and 21B," should read "as shown in Figures 20A and 20B".

6. On page 20, [0073], line 2, the instance where it reads "22C", should read "21C". Figure 22C does not exist.

Appropriate correction is required.

Claim Rejections - 35 USC § 102

1. The following is a quotation of the appropriate paragraphs of 35 U.S.C. 102 that form the basis for the rejections under this section made in this Office action:

A person shall be entitled to a patent unless -

- (b) the invention was patented or described in a printed publication in this or a foreign country or in public use or on sale in this country, more than one year prior to the date of application for patent in the United States.
- 2. Claims 1-4, 7 and 14 are rejected under 35 U.S.C. 102(b) as being anticipated by WO 02/068104 to Higuchi (submitted on the Information Disclosure Statement on 10 September 2004, herein referred "Higuchi").
- 3. WO 02/068104 has an English equivalent US Pub. No. 2006/0079585. All rejections are based off the English equivalent translation 2006/0079585.
- 4. Regarding claim 1, the reference Higuchi discloses a process and apparatus for rapidly producing an emulsion and microcapsules in a simple manner. The microcapsules include a step of feeding a shell-forming phase to a continuous phase. A dispersion phase is ejected toward the junction of the flow of a first and second continuous phase flowing in the microchannels. The dispersion phase joins the flows of

Art Unit: 1709

the first and second continuous phase and produces a microdroplet (see Figure 6, abstract, page 1 [0007], page 4 [0060-0061]).

- 5. Regarding claims 2-4, the reference Higuchi discloses that the flows used in the apparatus in the continuous phase can be oil and the dispersion phase can be water (see page 3 [0055]). It is known in the art that oil and water are immiscible solutions.
- 6. Regarding claim 7, the reference Higuchi discloses that the continuous phase is a solution of oil containing 70% oleic acid (see page 3 [0053]). It is known in the art that oleic acid is an amphiphilic molecule.
- 7. Regarding claim 14, the reference Higuchi discloses that microdroplets with a specific size of 25 μ m can be obtained when the pressure of the dispersion phase is set to 2.45 kPa and the continuous phase is set to 4.85 kPa. When the pressure changes in the continuous phase, changes the diameter of the microdroplets produced can be altered (see page 3 [0053]). It is interpreted by the examiner that an increase in pressure of the phases, the greater the shear force is created, overcoming interfacial forces of another stream.
- 8. Claims 21-22 are rejected under 35 U.S.C. 102(b) as being anticipated by CA 2 304 644 to Klinksiek et al.
- 9. Regarding claim 21, the reference Klinksiek discloses a device for producing a silicone and/or silane emulsion wherein there is a mixing station for the emulsion components are delivered by pumps through nozzles that mix a jet of an active agent with an aqueous phase to produce an emulsion (see abstract). As seen in Figure 1, the

device includes first microchannel where silicon oil (1) is injected and a second and third microchannels where an aqueous phase (3) is injected. The three microchannels form a junction in the nozzle (4), where the nozzle arrangement is fed by means of two pumps to a channel downstream (see page 6, lines 21-30 and Figure 1).

Page 6

10. Regarding claim 22, the reference Klinksiek discloses the nozzle arrangement in the device is delivered by means of two pumps with a pressure difference of 2-3 bar where the coating of the emulsifier permit the aqueous emulsifier solution and the silicone to be fed together in the final emulsion concentration and homogenized directly by means of a jet disperser (see page 6, lines 28-30 and page 7, lines 1-2).

Claim Rejections - 35 USC § 103

- 11. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:
 - (a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.
- 12. The factual inquiries set forth in *Graham* v. *John Deere Co.*, 383 U.S. 1, 148 USPQ 459 (1966), that are applied for establishing a background for determining obviousness under 35 U.S.C. 103(a) are summarized as follows:
 - 1. Determining the scope and contents of the prior art.
 - 2. Ascertaining the differences between the prior art and the claims at issue.
 - 3. Resolving the level of ordinary skill in the pertinent art.
 - Considering objective evidence present in the application indicating obviousness or nonobviousness.

Page 7

prior art under 35 U.S.C. 103(a).

13. This application currently names joint inventors. In considering patentability of the claims under 35 U.S.C. 103(a), the examiner presumes that the subject matter of the various claims was commonly owned at the time any inventions covered therein were made absent any evidence to the contrary. Applicant is advised of the obligation under 37 CFR 1.56 to point out the inventor and invention dates of each claim that was not commonly owned at the time a later invention was made in order for the examiner to

14. Claims 5-6 and 13 are rejected under 35 U.S.C. 103(a) as being unpatentable over Higuchi as applied to claim 1 above, and further in view of Klinksiek.

consider the applicability of 35 U.S.C. 103(c) and potential 35 U.S.C. 102(e), (f) or (g)

- 15. Regarding claim 5, the reference Higuchi discloses the claimed invention except for dissolving a reagent in the first solution. Klinksiek teaches that it is known in the art to prepare a fine particle and stable silicone emulsion of oil in water. Prior to homogenization, silicon is introduced slowly with stirring into an aqueous emulsifier mixture before the resulting coarse-particle emulsion undergoes actual homogenization (see page 1, lines 3-5 and 12-14). It would have been obvious to one having ordinary skill in the art at the time the invention was made to dissolve a reagent in the aqueous solution to create a mixture for the water phase before emulsion to produce a microparticle with a composition of interest.
- 16. Regarding claim 6, the reference Higuchi discloses the claimed invention except for where the added reagent to the aqueous solution is a drug. Klinksiek teaches that it

Art Unit: 1709

is known in the art to slowly stir in silicon particles into an aqueous solution (see page 1, lines 12-14). It would have been obvious to one having ordinary skill in the art at the time the invention was made to add a drug reagent instead of silicon particles to the aqueous solution to produce microparticles with a drug rather than silicone.

- 17. Regarding claim 13, the reference Higuchi discloses the claimed invention except for where a polymer molecule is dissolved in the second solution. Klinksiek teaches that it is known in the art to stir in silicon particles into an aqueous solution (see page 1, lines 12-14). It would have been obvious to one having ordinary skill in that art at the time the invention was made to add a polymer to the second solution as there was silicon mixed into an aqueous solution to create a silicone and/or silane emulsion to change the content of the microdroplet formed after a collision of the continuous and dispersion phases.
- 18. Claims 8-11 are rejected under 35 U.S.C. 103(a) as being unpatentable over Higuchi as applied to claim 1 above, and further in view of Handa et al. (herein referred "Handa").
- 19. Regarding claims 8-9, the reference Higuchi discloses the claimed invention except for producing a mono- and bi- layer vesicle with an amphiphilic molecule. Handa discloses a method for producing a phospholipid monolayer at the triolein saline interface that is converted into a bilayer through differential quenching of N-dansyl-PE (see abstract and page 2888, left column, Formation of Microemulsion). It would have been obvious to one having ordinary skill in that art at the time the invention was made

Art Unit: 1709

to produce a monolayer vesicle and convert it into a bilayer vesicle in order to determine the stability of the monolayer and to examine the properties of the bilayer in the pharmaceutical, chemical or medicine fields.

- 20. Regarding claims 10-11, the reference Higuchi discloses the claimed invention except for using different types of amphiphilic molecules in the production of the vesicles. Handa discloses that in experimentation, the interfacial tensions of phospholipids include phosphatidylcholine, phosphatidylethanolamine and phosphatidylserine, in the triolein saline emulsion (see abstract). It would have been obvious to one having ordinary skill in that art at the time the invention was made to examine different amphiphilic molecules to determine the stability and interfacial tension of the monolayers of each lipid for purposes of testing in pharmaceutical, chemicals or medicines.
- 21. Claim 12 is rejected under 35 U.S.C. 103(a) as being unpatentable over Higuchi and Handa as applied to claim 9 above, and further in view of Klinksiek.
- 22. The reference Higuchi and Handa disclose the claimed invention except for the first and second solution interface is formed by a third solution flowing downstream through two downstream input channels. Klinksiek discloses a device for producing silicon and/or siliane emulsions where a silicone oil is injected into the aqueous phase via a nozzle and is immediately afterwards mixed intensively and homogenized in a second nozzle. A final fine dispersion takes place in the downstream jet disperser (see page 6, lines 21-30, Figure 6). The device in Figure 6 is capable of having an inlet

Art Unit: 1709

stream moved downstream to allow a microdroplet from the first two streams and then a new microdroplet from a third inlet stream. It would have been obvious to one having ordinary skill in that art at the time the invention was made to construct the microchannels in a way where the inlet steams are joined together to produce a bilayer vesicle where the two inlets are joined immediately and a third is joined downstream to allow time to form the first monolayer vesicle.

- 23. Claim 15 is rejected under 35 U.S.C. 103(a) as being unpatentable over Higuchi as applied to claim 14.
- 24. Regarding claim 15, the reference Higuchi discloses the claimed invention but does not explicitly disclose increasing the flow rates of the second and third stream. Higuchi discloses changing the pressure of the dispersion and continuous phases to alter the size of the microdroplets, and it would have been obvious to one having ordinary skill in the art at the time the invention was made to alter the flow rates of the continuous phases to alter the microdroplet sizes while changing the pressures of the phases.
- 25. Claim 16 is rejected under 35 U.S.C. 103(a) as being unpatentable over Higuchi as applied to claim 1 above, and further in view of Nisisako et al. (submitted on the Information Disclosure Statement on 10 September 2004, herein referred "Nisisako").
- 26. Regarding claim 16, the reference Higuchi discloses the claimed invention except for controlling flow rates of the three inlet streams. Nisisako teaches that it is known in

Art Unit: 1709

the art to prepare microdroplets inside a liquid layer at a T-junction in a microchannel network and observing the flow speed (average velocity) and the droplet size in the continuous phases (see page 958, section 3.1). It would have been obvious to one having ordinary skill in the art at the time the invention was made to alter the continuous phase and dispersion phase flow rates of the microchannel set up either it be a T-junction or a set up with three microchannels comprising of two continuous phases and one dispersion phase to observe the change in droplet size produced in relation to the flow rates.

- 27. Claims 17–20 are rejected under 35 U.S.C. 103(a) as being unpatentable over Higuchi and Nisisako as applied to claim 13 above, and further in view of Klinksiek.
- 28. Regarding claim 17, the reference Higuchi and Nisisako disclose the claimed invention except for the flow rates being controlled by one or more pumps. Klinksiek teaches that it is known in the art to produce a silicone emulsion that is delivered by pumps with different pressure differences (see page 6, line 28-29). It would have been obvious to one having ordinary skill in the art at the time the invention was made to use pumps to deliver a continuous stream of pressure to the microchannels to produce microdroplets.
- 29. Regarding claim 18, the references Higuchi and Klinksiek disclose the claimed invention except for manipulating the flow rate of the first solution to control the rate of the droplet formation. Nisisako teaches that it is known to change the flow speed of the continuous phase to change the droplet size. The droplet size decrease as the average

Art Unit: 1709

velocity increases of the continuous phase (see page 958, section 3.1). It would have been obvious to one having ordinary skill in that art at the time the invention was made to change the flow rate of the dispersion phase with an aqueous solution to change the size of the droplet, rather than the continuous phase flow rate.

- 30. Regarding claims 19-20, the references Higuchi and Klinksiek disclose the claimed invention except for increasing the flow rate of the second solution to decrease the size of the droplets formed. Nisisako teaches that it is known in the art that at a given dispersed phase, the droplet size decreases as the average velocity (flow speed) increase of the continuous phase flow (see page 958, section 3.1 and Figure 3). In Figure 3, the graph shows the effect on the droplet size of the continuous phase flow, either increasing or decreasing. As the size of the droplet decreases, the continuous phase flow speed increases. The continuous phase flow content was high and oleic sunflower oil was used as the oil phase. It would have been obvious to one having ordinary skill in the art at the time the invention was made to change the flow speed of the continuous phase flow at a constant dispersed phase to change the droplet size produced.
- 31. Claims 23 and 25-26 are rejected under 35 U.S.C. 103(a) as being unpatentable over Klinksiek as applied to claim 22 above.
- 32. Regarding claim 23, the reference Klinksiek discloses the claimed invention except for controlling the flow rates of each of the three inlet microchannles by adjusting the three pumps. Klinksiek discloses the device that feeds the aqueous and oil solutions is fed by two pumps (see page 6, line 28). It would have been obvious to one

/

Art Unit: 1709

having ordinary skill in the art at the time the invention was made to have each solution in each microchannel fed by individual pumps to monitor or change the flow of each phase to alter the size of the microdroplets through the collision of particles.

- 33. Regarding claim 25-26, the reference Klinksiek discloses the claimed invention except for varying the viscosity of the second solution. Klinksiek discloses an oil in water emulation where an emulsion mixture where there is silicone introduced slowly with stirring into an aqueous emulsifier mixture (see page 1, lines 12-13). It is interpreted by the examiner that adding silicone to the aqueous solution changes the viscosity of the first solution. It would have been obvious to one having ordinary skill in the art at the time the invention was made to add a reagent or polymer into the second oil solution varying the viscosity of the solution to change the flow rate of the phase and size of the particles produced.
- 34. Claim 24 is rejected under 35 U.S.C. 103(a) as being unpatentable over Klinksiek as applied to claim 22 above, and further in view of Nisisako.
- 35. Klinksiek discloses the claimed invention except for varying the dimensions of the microchannel junction. Nisisako discloses a method for preparing microdroplets inside the liquid layer at a T-junction in a microchannel network by changing the channel size to change the droplet size formation. In Figure 4, the graph shows the effect of the width of the continuous phase channel (see Figure 4 and page 958, section 3.2). It would have been obvious to one having ordinary skill in the art at the time the invention was made to not just change the size of the continuous phase channel but also the

Art Unit: 1709

microchannel junction of the dispersed and continuous phase to observe the change in velocity profile and droplet size.

- 36. Claims 27-28 are rejected under 35 U.S.C. 103(a) as being unpatentable over Klinksiek as applied to claim 21 above, and further in view of EP 1 358 931 A2 to Kawai et al. (submitted on the Information Disclosure Statement on 10 September 2004, herein referred "Kawai").
- 37. Regarding claims 27-28, the reference Klinksiek discloses the claimed invention except where the input first channel is in an orientation where it is less than or equal to 60 degrees to the second and third input microchannels. Kawai disclose a fine channel device system (Figure 5) where there are two dispersion phases and one continuous phase at a junction where there are fine particles formed and flow in a fine channel (see page 7, lines 22-25, Figure 5). In Figure 5, the three channels are in an orientation where the first, second and third microchannels are arranged less than 60 degrees from each other. An inlet channel for feeding the dispersion phase characterizes the fine channel device and the inlet channel for feeding the continuous phase are joined at an arbitrary angle (see page 8, lines 44-46). It would have been obvious to one having ordinary skill in the art at the time the invention was made to arrange the device to produce microdroplet such that the three microchannel are arranged less than 60 degrees from each other to produce a smooth flow of phases when at the microchannel junction that later flow downstream.

.....

Art Unit: 1709

38. Claim 29 is rejected under 35 U.S.C. 103(a) as being unpatentable over Klinksiek as applied to claim 21 above, and further in view of Higuchi.

- 39. Regarding claim 29, the reference Klinksiek discloses the claimed invention except where the microchannel junction is greater than the widths of the three input microchannels. Higuchi discloses an apparatus for producing an emulsion and microcapsules where there are two input channels for continuous phase flows and one input channel for the dispersion phase flow. In Figure 6, the width of the junction of the three flow channels is greater than the widths of each individual microchannel (see Figure 6). It would have been obvious to one having ordinary skill in the art at the time the invention was made to construct the device to produce microdroplets with three input microchannels with the junction greater than the individual microchannels to allow the optimum space for emulsion and maintain the flow speed when collision occurs between the water and oil particles.
- 40. Claim 30 is rejected under 35 U.S.C. 103(a) as being unpatentable over Klinksiek as applied to claim 21 above, and further in view of Tan et al (submitted on the Information Disclosure Statement on 10 September 2004, herein referred "Tan").
- 41. Klinksiek discloses the claimed invention except for the output channel has a bowtie shape. Tan discloses a microfluidic device, which could embody different variation of channel designs. In Figure 4A there is a bowtie channel where the emulsions are generated at the cross junction allowing the size of the droplet emulsion to be manipulated by the flow rate of the oil phase (see page 2, Figure 4A). It would

Art Unit: 1709

have been obvious to one having ordinary skill in the art at the time the invention was made to construct the output channel in a bowtie shape in order to manipulate the size of the droplet and flow of the emulsions.

- 42. Claims 31-33 is rejected under 35 U.S.C. 103(a) as being unpatentable over Higuchi, and further in view of USP 6,211,654 to Quake (herein referred "Quake").
- 43. Regarding claim 31,the reference Higuchi discloses the claimed invention except for processing the droplet. Higuchi discloses a process and apparatus for rapidly producing an emulsion and microcapsules in a simple manner. The microcapsules include a step of feeding a shell-forming phase to a continuous phase. A dispersion phase is ejected toward the junction of the flow of a first and second continuous phase flowing in the microchannels. The dispersion phase joins the flows of the first and second continuous phase and produces a microdroplet (see Figure 6, abstract, page 1 [0007], page 4 [0060-0061]). Quake discloses a device for analyzing and sorting polynucleotides by size (see abstract and column 1, line 14-17). It would have been obvious to one having ordinary skill in the art at the time the invention was made to produce a microdroplet from the sandwiching of three streams and process the droplet formed for analyzing purposes.
- 44. Regarding claims 32-33, the reference Higuchi discloses the claimed invention except for processing the droplet generated from the first stream. Quake discloses a microfabricated device for analyzing and sorting the polynucleotide by size (see abstract and column 1, line 14-17). It would have been obvious to one having ordinary skill in

Art Unit: 1709

the art at the time the invention was made to produce microdroplets by sheath flow then analyze and sort the particles by size to determine different sizes produced from the sandwiching of three input streams.

- 45. Claims 34-37 are rejected under 35 U.S.C. 103(a) as being unpatentable over Higuchi and Quake as applied to claim 31 above, and further in view of USP 6,733,172 to Lee (herein referred "Lee").
- 46. Regarding claims 34-36, the references Higuchi and Quake disclose the claimed invention except for splitting the droplets into equal or unequal sizes. Lee discloses a magnetohydrodynamic fluidic system that splits droplets in a MHD microfluidic channel (see column 5, lines 65-66). An initial droplet in the droplet splitter channel is moved along the microfluidic channel by utilizing a sequential set of MHD pumps. The pumps provide a MHD micropump in which the Lorentz force is used to propel the droplet along the microchannel. The droplet is stretched into separate droplets by control of the MHD pumps that are selectively activated to stretch the droplet until the components are separate (see column 6, lines 1-6 and 21-31). Since the controls are selectively activated the droplet splitter is capable of producing equal and unequal sized droplets by activating particular pumps to stretch and separate the components. It would have been obvious to one having ordinary skill in the art at the time the invention was made to split a droplet into smaller components for minuscule sampling or testing of droplets.
- 47. Regarding claim 37, the reference Higuchi and Quake disclose the claimed invention except for the processing comprises of fusing two or more droplets together.

Art Unit: 1709

Lee discloses a droplet mixer where one droplet is stretched into two component sections and a second droplet is moved into contact with the droplet and by use of MHD pumps the two droplets are combine to form a mixed material (see column 6, lines 43-56, Figure 3A-B). It would have been obvious to one having ordinary skill in the art at the time the invention was made to fuse two droplets together to form a larger droplet either mixing materials or creating a larger droplet for analysis.

- 48. Claims 34-36 are rejected under 35 U.S.C. 103(a) as being unpatentable over Higuchi and Quake as applied to claim 31 above, and further in view of WO 2004/002327 to Stone et al. (submitted on the Information Disclosure Statement on 10 September 2004, herein referred "Stone").
- 49. Regarding claims 34-36, the references Higuchi and Quake disclose the claimed invention except for splitting the droplets into equal and unequal sizes. Stone discloses a microfluidic device and method for forming a discontinuous section of similar or dissimilar size in a fluid provided (see abstract). In a plurality of microchannels, each carrying a plurality of subject droplet are moved along the channel toward a different arrangement of obstruction to form a variety of different sized droplets. As the droplet flows through the channel, it is free from obstruction and its flow is unaffected. In the different channels, depending on the arrangement of the obstructions, the sizes of the new droplets downstream of the obstructions can be of equal/uniform size or unequal sizes. This occurs when the larger droplet comes in contact with the obstruction(s) (see page 19, lines 15-33; Figure 6). It would have been obvious to one having ordinary skill

Art Unit: 1709

in the art at the time the invention was made to incorporate obstructions in different patterns in the outlet channels of the newly formed microdroplet emulsions to split or form discontinuous sections of similar or dissimilar fluid particles.

- 50. Claim 38 is rejected under 35 U.S.C. 103(a) as being unpatentable over Higuchi and Klinksiek, and further in view of USP 6,540,895 to Spence (herein referred "Spence").
- 51. Regarding claim 38, the reference Higuchi and Klinksiek disclose the claimed invention except for a droplet processor. Higuchi discloses a process and apparatus for rapidly producing an emulsion and microcapsules in a simple manner. The microcapsules include a step of feeding a shell-forming phase to a continuous phase. A dispersion phase is ejected toward the junction of the flow of a first and second continuous phase flowing in the microchannels. The dispersion phase joins the flows of the first and second continuous phase at a junction and produces a microdroplet (see Figure 6, abstract, page 1 [0007], page 4 [0060-0061]). Klinksiek discloses a device for producing a silicone and/or silane emulsion where the components are fed by the means of two pumps, one for the two aqueous phases and one for the silicone oil. The dispersion of the emulsion that is formed is dispersed in a downstream jet (see page 6, lines 21-29). Spence discloses a microfacricated device for sorting cells based on a desired characteristic such as reporter labeled cells and can be sorted by the presence or level of the reporter on the cell. Along the main channel of the sample inlet there is a detection region that is in communication with processor (computers and software) to

Art Unit: 1709

detect a signal representative of cell characteristics (see abstract and column 8, lines 27-29 and 36-37). It would have been obvious to one having ordinary skill in the art at the time the invention was made to use a detection system that detects cell characteristics with a computer, where data can be stored and processed, to be used in the analysis of microdroplets that are produced from the multiple input microchannels with the aid of pumps.

- 52. Claim 39 is rejected under 35 U.S.C. 103(a) as being unpatentable over Higuchi and Klinksiek as applied to claim 38 above, and further in view of Lee and USP 2002/0058332 to Quake and Thorsen (submitted on the Information Disclosure Statement on 10 September 2004, herein referred "Thorsen").
- 53. The references Higuchi and Klinksiek disclose the claimed invention except for where the droplet splitter has two or more daughter channels in communication with the splitter input channel. Thorsen discloses a microfluidic device for analyzing and/or sorting biological materials with a main channel and branch channels (see page 8 [0077]). Lee discloses a device where there are MHD pumps located along the microchannels that are capable of moving the droplet in the microchannel to the desired location or splitting the droplet (see column 6, lines 21-24 and Figure 2B). It would have been obvious to one having ordinary skill in that art at the time the invention was made to combine the microfluidic device of Thorsen and the MHD pumps of Lee along the walls of the microchannels to move the droplets to desired locations along the channels

Art Unit: 1709

and split the droplet at the precise location to allow each split droplet flow down each daughter/branch channel.

- 54. Claim 40 is rejected under 35 U.S.C. 103(a) as being unpatentable over Higuchi and Klinksiek as applied to claim 38 above, and further in view of Quake.
- 55. Regarding claim 40, the reference Higuchi and Klinksiek disclose the claimed invention except for droplet processor that comprises of droplet sorter. Quake discloses a microfabricated device that analyzes and sorts single polynucleotides by size. The device has a solution inlet that has a plurality of branch channels that are in fluid communication and branch out from the discrimination region. The flow of molecules is maintained through the device via a pump of pressure differential and a directing means comprising of a valve structure at the branch point effective to permit the molecule to enter only one of the branches (see column 2, lines 49-51, 63-67, column 7, line 8, 14-20 and Figure 1). It would have been obvious to one having ordinary skill in that art at the time the invention was made to sort the droplets that are formed via an input channel and daughter channels that are regulated via pumps to maintain a flow and a pressure gradient to avoid the droplets in the device from being stagnant.
- 56. Claim 41 is rejected under 35 U.S.C. 103(a) as being unpatentable over Higuchi and Quake as applied to claim 38 above, and further in view of Lee.
- 57. Regarding claim 41, the references Higuchi and Quake disclose the claimed invention except for the droplet processor comprises of a droplet fuser. Lee discloses a

Art Unit: 1709

magnetohydrodynamic fluidic system that mixes droplets. The droplet mixer disclosed is enhanced by stretching one droplet to engulf another. A first droplet is introduced into a microchannel and moved along the channel by a set a MHD pumps and stretched into two separate component sections. A second droplet is introduced into another microchannel and moved toward the first stretched droplet by use of the MHD pumps and moved into contact with the first droplet between the two separate component sections of the droplet. The set of MHD pumps are used to combine the droplet to form a mixed material (see column 6, lines 43-56; Figures 3A-B). It would have been obvious to one having ordinary skill in the art at the time the invention was made to fuse together two microparticles in a device to form a larger particle with either different or identical concentrations to produce a well-mixed particle for analysis.

Conclusion

Any inquiry concerning this communication or earlier communications from the examiner should be directed to Christine T. Mui whose telephone number is (571) 270-3243. The examiner can normally be reached on Monday-Friday 8-5; Alternate Friday.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Walter Griffin can be reached on (571) 272-1447. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Art Unit: 1709

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

CTM

WALTER D. GRIFFIN SUPERVISORY PATENT EXAMINER